


## Features:

- DC constant output voltage, 100% full load burn-in test
- AC input range selectable by switch
- Protections: Short circuit/Over load/Over temperature
- Cooling by free air convection
- Compact size, light weight
- Fixed switching frequency at 25KHz
- Low cost
- High reliability




**LMPS - 1**



LUMITRON REF.	Input Voltage	Output Voltage	Size (LxWxH)
LMPS-1-12W-12V	85-264V	12VDC	70x39x30
LMPS-1-25W-12V	85-264V	12VDC	85x58x38
LMPS-1-35W-12V	85-264V	12VDC	85x58x38
LMPS-1-50W-12V	85-264V	12VDC	88x70x38
LMPS-1-120W-12V	176V-264V	12VDC	199X98X40
LMPS-1-120W-24V	176V-264V	24VDC	199X98X40



**LMPS - 2**



LUMITRON REF.	Input Voltage	Output Voltage	Size (LxWxH)
LMPS-2-200W-12V	90-264V	12VDC	215x115x50
LMPS-2-200W-24V	90-264V	24VDC	215x115x50
LMPS-2-250W-12V	90-264V	12VDC	215x115x50
LMPS-2-250W-24V	90-264V	24VDC	215x115x50
LMPS-2-350W-12V	90-264V	12VDC	215x115x50
LMPS-2-350W-24V	90-264V	24VDC	215x115x50